

RXeco FORCE

380e - 450e - 500e

Ultra strong two motor carpet cleaner for large areas

STRENGTHS

- › Selected by the White House U.S.A.
- › Strong and reliable –ideal for contract cleaners
- › 5 levels of filtration with HEPA filter (optional)
- › Accessories on board
- › Double body/base support with quick release
- › Stainless steel guides anti wear
- › Available in 3 sizes: 380 (15 "), 450 (18 "), 500 (20 ")
- › Energy consumption combined: class "B "



eco FORCE



機器規格資料

	RX 380e	RX 450e	RX 500e
耗電量 (W)	930	950	950
真空壓 mm/H ₂ O (in/H ₂ O)	2300 (90)	2300 (90)	2300 (90)
吸入風量 lt/sec (CFM)	49 (103.8)	49 (103.8)	49 (103.8)
馬達保護裝置	溫控/電流	溫控/電流	溫控/電流
集塵紙袋容量 (lt.)	4	4	4
不織布集塵袋	選購配件	選購配件	選購配件
3M 排氣過濾網	標準配件	標準配件	標準配件
高效率過濾器 (Hepa H11)	選購配件	選購配件	選購配件
齒狀驅動皮帶	標準配件	標準配件	標準配件
電子負載保護	標準配件	標準配件	標準配件
聚塵式清潔刷/轉速 (RPM)	5000	4500	4500
滾刷蹄座	不鏽鋼	不鏽鋼	不鏽鋼
清潔效率 m ² /H (sq.ft/H)	630 (6700)	750 (8000)	850 (9100)
噪音值 (db)	68.6	68.6	68.6
總重 Kg (lb)	7,79 (17.2)	8,16 (17.9)	8,25 (18.2)
電線長度 mt. (ft.)	10 (41)	10 (41)	10 (41)
耗能等級 (Class)	B	B	B

1. Electronic control provides for a soft start, overload indication for the correct height adjustment and motor shut off.
2. The dynamically balanced roller and metal supports with ball bearings can be quickly replaced without tools. The RX is equipped with 4 rubber wheels as well as two side cylinders to glide flush with the wall. Two wear resistant stainless steel base guides provide a shockproof system. Two position operation provides easy transition over thresholds.
3. Air and dust are highly filtered and special attention was given to the power nozzle with a washable entry/exit cooling air filter – easily replaced without tools.
4. Thanks to the stretch hose and the telescopic wand on board, is possible to connect the M28R hard floor tool.



權能國際股份有限公司

新北市三重區興德路86號4樓(遠見科技大樓)

電話: 02-29957337(代表) 傳真: 02-29957031

www.joynice.com.tw

inf@joynice.com.tw