

專業自動洗地機

CT70



清潔劑由刷盤中心 順刷盤轉動平均噴灑 不浪費及污漬牆角



機械性浮動刷盤設計 適宜任何不平整地面清潔 使機器保持最佳清潔效率



V形水刮組設計 集水/吸水效率佳



直覺式簡易操作 符號及符合人體 工學設計

獨特科技設計

TCL微電腦充電器



補充式充電設計,有效管理電池使用效能 及延長電池組獨立使用年限





全自動操作功能程式設計: 出水系統/清洗刷/吸水馬達 同步啟動/關閉 吸水馬達延遲關閉設計



清洗刷裝卸/吸水膠片/水管 更新,皆不需使用任何工具

電池組



搭載AGM-EV等級深度放電免保養電池,可節省保養費用及減低耗損成本,電池材質採100%可回收物料

定量式清潔劑劑量調配器(選購)



清潔劑供應系統與供應水槽分離設計可精確供應清潔劑量,節省成本 清潔劑供應桶不需工具即可裝/卸



清潔劑出水量及 機器前進速度可 依據工作需求微調



特殊防泡沫系統有效保護 •當污水槽水位滿即自動

• 清水槽無供應水時即 自動停機

停止吸水



吸水刮組配備防刮牆角 導輪,95%乳膠材質吸 水膠片堅固耐用,特殊設 計可四面更 替使用



黃色保養區域指示 及清洗刷毛耗損紅色 指示,使保養更簡便



搭載雙具齒輪箱清洗 馬達及高品質電路系 統設計

Main technical characteristics

Motors

- Brush rotation: independent oil bath motor gear box
- Suction: 2 stages with stainless steel fans and shaft
- Traction: parallel axis differential with stainless steel bearings

Plastics

- Tanks: great thickness high density polyethylene
- Squeegee blades: made in Latex usable on 4 sides
- Hoses: suction and discharge made in high resistance polyurethane
- Wheels: oil resistant

Other characteristics

- Nylon standard brushes with maximum consumption indicator
- Automatic brush click-on/off
- Electronic solution flow adjustment
- Positioned in height discharge hose (ø 40 mm)

Mechanics

- Chassis: double treatment with galvanizing + die-casting
- Bearings: shielded against humidity and water seepages
- Bolts and nuts: made in stainless steel where there are water contacts

Electric system

- Carbon brushes: easily changeable
- Boards: equipped with protective film against water and humidity
- Solenoid valve: with Viton membrane resistant against chemical agents
- Sensors: solution and recovery water level protected against accidental impacts
- Display: digital with hour counter and battery level



Control panel Brushes, solution and vacuum inserted by one unique command or singularly upon necessity

機型	清洗寬度 (mm)	吸水寬度 (mm)	清洗效率 (㎡/h)	刷盤數量	清水容量 (I)	污水容量 (I)	電力	前/後進 速 度 (Km/h)	淨重 (Kg)	體積 (LxWxH) (cm)
CT70 BT70	700	1010	3150	2	70	75	24V (2x12V)	4.5	95	1220x748x960

選購配件







